



# RL3200AR



SUBLIMATION SERIES

## INSPIRING INNOVATION



### MAIN APPLICATION

Decoration Industry

Advertising Industry

Interior Design Industry

Exhibition Industry

Garment & Textile Industry

SUBLIMATION SERIES

◀▶ **RL3200AR (1024i)**

JAPAN  
KONICA Print Head



HAPOND DIGITAL TECHNOLOGY SDN. BHD. (788546-V)

# RL3200AR

## SUBLIMATION SERIES



### TECHNICAL SPECIFICATIONS

Dimension 机器尺寸	6300mm(L/长) x 1450mm(W/宽) x 2000mm(H/高)		
Weight 机器重量	1850kg /公斤		
Max. Print Width 打印宽度	3200mm /毫米		
Ink Type 墨水类型	Sublimation Ink /热升华墨水		
Ink Color 墨水颜色			
Print Head 打印喷头	KONICA 1024i		
No. of Print Head 喷头数量	Max. 12 units		
Print Resolution 打印精度	2880dpi		
Printing Speed 印刷速度	Sketch Mode /草图模式	150 m <sup>2</sup> /h	225 m <sup>2</sup> /h
	Production Mode /生产模式	100 m <sup>2</sup> /h	150 m <sup>2</sup> /h
	High Precision Mode /高精度模式	75 m <sup>2</sup> /h	112 m <sup>2</sup> /h
Print Mode 打印模式	Uni- and Bi- Direction /单向和双向		
Media Type 适用材料种类	Non-flexi, Sublimation Fabric, Treated Polyester 无弹性热升华直喷面料, 处理过的聚酯纤维		
RIP & Control Software 软件输出	Hapond Printer Manager, PhotoPrint		
Cleaning System 清洗系统	Positive Purge each Color /单色正压清洗		
Drying System 烘干处理系统	Special Design Fan Drying System, Post Printing Heating System 特殊设计风扇干燥系统, 印后加热系统		
Image Format 打印文件格式	BMP, TIFF, JPEG, EPS, PDF, etc.		
Color Management 颜色控制	ICC Profile /ICC彩色特性文件		
Data Interface 数据传输	USB 2.0 / 3.0		
Input Voltage 输入电压	Single Phase, 50Hz/AC 220V ±10%, 32A (Printer+Heaters)		
Working Environment 工作环境	Temperature /温度	: 20°C~28°C	
	Humidity /湿度	: 40%~70%	

Technical specifications are subject to change without prior notice.



HAPOND DIGITAL TECHNOLOGY SDN. BHD. (788546-V)



+603-4296 3733



+603-4296 9733



sales@hapond.com.my



hapond.com.my



facebook.com/haponddigital



21, Jalan Bukit Permai Utama Tiga,  
Taman Industri Bukit Permai, Cheras,  
56100 Kuala Lumpur, Malaysia.

