



TP-200X



SUBLIMATION SERIES

INSPIRING INNOVATION



MAIN APPLICATION

Decoration Industry

Advertising Industry

Interior Design Industry

Exhibition Industry

Garment & Textile Industry

SUBLIMATION SERIES

◀ TP-200X (512i / 1024i)

JAPAN
KONICA Print Head



HAPOND DIGITAL TECHNOLOGY SDN. BHD. (788546-V)

TP-200X

SUBLIMATION SERIES



TECHNICAL SPECIFICATIONS

Dimension 机器尺寸	3720mm(L/长) x 1100mm(W/宽) x 1830mm(H/高)		
Weight 机器重量	900kg /公斤		
Max. Print Width 打印宽度	2000mm /毫米		
Ink Type 墨水类型	Sublimation Ink /热升华墨水		
Ink Color 墨水颜色			
Print Head 打印喷头	KONICA 512i (6pl/13pl), Optional: KONICA 1024i (6pl/13pl)		
No. of Print Head 喷头数量	4 / 8 units		
Print Resolution 打印精度	Max up to 1440/2880dpi		
Printing Speed 印刷速度	Production Mode /生产模式	60 m ² /h	120 m ² /h
	Quality Mode /品质模式	45 m ² /h	90 m ² /h
	High Precision Mode /高精度模式	30 m ² /h	60 m ² /h
Print Mode 打印模式	Uni- and Bi- Direction /单向和双向		
Media Type 适用材料种类	Non-flexi, Sublimation Fabric /无弹性热升华直喷面料		
RIP & Control Software 软件输出	Hapond Printer Manager, PhotoPrint		
Cleaning System 清洗系统	Positive Purge each Color /单色正压清洗		
Drying System 烘干处理系统	Special Design Fan Drying System, Post Printing Heating System 特殊设计风扇干燥系统, 印后加热系统		
Image Format 打印文件格式	BMP, TIFF, JPEG, EPS, PDF, etc.		
Color Management 颜色控制	ICC Profile /ICC彩色特性文件		
Data Interface 数据传输	USB 2.0 / 3.0		
Input Voltage 输入电压	Single Phase, 50Hz/AC 220V ±10%, 32A (Printer+Heaters)		
Working Environment 工作环境	Temperature /温度 : 20°C~28°C Humidity /湿度 : 40%~70%		

Technical specifications are subject to change without prior notice.



HAPOND DIGITAL TECHNOLOGY SDN. BHD. (788546-V)

