

# 3S CUTTING PLOTTER





#### **MAIN APPLICATION**

**Decoration Industry** 

Advertising Industry

Packaging Industry

Gift Industry

### **FINAL PRODUCT**







## **3S CUTTING PLOTTER**



#### **TECHNICAL SPECIFICATIONS**

MODEL	3S CUTTING PLOTTER
Model	A13C
Interface	The USBU disk has two interface
Maximum feed width	335mm
Maximum cutting width	320mm
Margin size	Leave 5mm white on each side of the material
Mark	5mm dot marking/camera recognition
Pages of material	Can hold 100 sheets of material/18mm thick
Motherboard	High speed microprocessor with 4Mb cache
Display	2*16 Chinese and English HD character LCD / 1.7-inch camera special LCD
Drive	Digital stepper motor, micro-step drive
Control panel	Film switch (life 1,000,000 cycles)
Drawing instruction	DMPL/HP-GL
Maximum cutting speed	800mm/s
Maximum cutting thickness	1mm
Knife pressure	50g-800g(160-grade digital cycle adjustment)
Power supply	AC90-240V/50Hz-6Hz
Mechanical accuracy	The 0.025 mm
Repetition accuracy	(+/- 0.1 mm
Net weight. / Gross weight	25kg/30kg
External dimensions	765*570*365mm/877*525*400mm
Support direct output of CDR	X4-X8, 2017-2022
Support direct Al output	CS6-2022
Support Windows system	WIN7-WIN11

Technical specifications are subject to change without prior notice.













